


# Directional Discrete TGSi Bladed Polyurethane



## COLOUR VARIATIONS



AS/NZ 1428.4.1 2009  
STANDARD



P5 SLIP RATING NATA  
APPROVED LAB



2 YEAR PRODUCT  
WARRANTY



INSTALLATION SERVICE  
AVAILABLE



REQUIRES 45%  
LUMINANCE CONTRAST  
Testing Services Available

SPECIFICATION	10mm Shaft	15mm Shaft
Beige	DDPL-10B-TSA-BEI	DDPL-15B-TSA-BEI
Black	DDPL-10B-TSA-BLK	DDPL-15B-TSA-BLK
Blue	DDPL-10B-TSA-BLU	DDPL-15B-TSA-BLU
Charcoal	DDPL-10B-TSA-CHA	DDPL-15B-TSA-CHA
Grey	DDPL-10B-TSA-GRY	DDPL-15B-TSA-GRY
Terracotta	DDPL-10B-TSA-TER	DDPL-15B-TSA-TER
White	DDPL-10B-TSA-WHI	DDPL-15B-TSA-WHI
Yellow	DDPL-10B-TSA-YEL	DDPL-15B-TSA-YEL

## SUITABLE SUBSTRATES

Concrete	Exposed Aggregate
Bitumen	Pavers

