


Directional Discrete TGSI Single Stem Polyurethane



COLOUR VARIATIONS



AS/NZ 1428.4.1 2009
STANDARD



P5 SLIP RATING NATA
APPROVED LAB



2 YEAR PRODUCT
WARRANTY



INSTALLATION SERVICE
AVAILABLE



REQUIRES 45%
LUMINANCE CONTRAST
Testing Services Available

Tactile Systems Australia Directional Discrete TGSI Polyurethane range are the ideal cost effective product for a wide range of applications. Available in a range of colours, they feature a P5 slip resistance rating – as tested by a NATA Approved Laboratory.

Manufactured from UV stabilised Thermoplastic Polyurethane Elastomer, which was specifically chosen to withstand the harsh Australian weather conditions and built environment.

SPECIFICATION

Beige	DDPL-20S-TSA-BEI
Black	DDPL-20S-TSA-BLK
Blue	DDLPL-20S-TSA-BLU
Charcoal	DDPL-20S-TSA-CHA
Grey	DDPL-20S-TSA-GRY
Terracotta	DDPL-20S-TSA-TER
White	DDPL-20S-TSA-WHI
Yellow	DDPL-20S-TSA-YEL

SUITABLE SUBSTRATES

Tiles	Carpet	Bitumen
Timber	Rubber	Concrete
Vinyl	Pavers	Exp Aggregate

