



AS/NZ 1428.4.1 2009  
Standard



P5 Slip Rating NATA  
Approved Lab



10 Year Product  
Warranty



Installation  
Service Available



Requires 45%  
Luminance Contrast

Warning Discrete TGSi

## Stainless Steel



### Design:

Truncated dome warning indicator with a concentric ring top for slip resistance.



### Material:

316 marine grade stainless steel.  
Black finish: PVD coat over 316 stainless








### Installation:

13mm or 25mm glue-in stem, pressure fit plug, screw fit, or flat base surface mount



### Suitable Substrates

Tiles, timber, vinyl, concrete, rubber, pavers and bitumen



### SPECIFICATIONS:

#### FLAT BASE

Silver WDSS-FB-TSA-SS

Black WDSS-FB-TSA-BLK

#### 13MM STEM

Silver WDSS-13S-TSA-SS

Black WDSS-13S-TSA-BLK

#### 25MM STEM

Silver WDSS-25S-TSA-SS

Black WDSS-25S-TSA-BLK

#### PRESSURE FIT

Silver WDSS-20P-TSA-SS

Black WDSS-20P-TSA-BLK

#### SCREW FIT

Silver WDSS-SF-TSA-SS

Black WDSS-SF-TSA-BLK

### VARIATIONS:

#### COLOURS

